

SKB's new Rolling Roto Shock Racks feature a (20" deep) roto molded tough shell with an integrally molded valance that eliminates the need for a metal valance on the outside of the case.

## FEATURES INCLUDE :

- Standard 19" rack width per EIA standards
- $\blacksquare$  Rack depth front to rear rail is 20" and each lid is 2-1/4" deep
- Threaded steel rails and aluminum cross components forming an "H" shaped rigid configuration
- Recessed Black powder coated twist latches with locking loops allow for opening while stacked
- Secure stacking design allows full use of doors while racks are stacked together
- 8 elastomeric shocks with a load range of from 40 lbs. to 150 lbs.)
- Load range may be increased up to 300 lbs. with optional additional HM-245 elastomeric shocks (see website for details)
- Gasket sealed front and rear doors
- Ambient pressure relief valve
- Sliding retractable handle
- Oversized snap-down handles on each side of the case
- Convenient roller blade wheels
- Cases stocked in Black
- Custom colors available (minimum quantities apply)
- \* Weight limits apply

Standard dimensions front to rear rail: 20"

Part #	Rack Units	Height	Lid Depth
3SKB-R02U20W	2 space	3-1/2"	2-1/4"
3SKB-R04U20W	4 space	7"	2-1/4"
3SKB-R06U20W	6 space	10-1/2"	2-1/4"
3SKB-R08U20W	8 space	14"	3-1/4"
3SKB-R10U20W	10 space	17-1/2"	3-1/4"
3SKB-R12U20W	12 space	21"	3-1/4"



elastomers



relief valves

MUSIC PRODUCTS 800.410.2024 SPORTS PRODUCTS 800.654.5992 INDUSTRIAL PRODUCTS 800.783.0087



www.skbcases.com