

The Lightweight E-Rack aluminum rack case is light yet robust and ideal for transporting critical, fragile rack equipment where weight, strength and portability are critical issues.

E-Rack is accredited to MIL-STD 810F and rated IP65. EMI Screening Characteristics accredited to IEEE STD 299-1997

Features:

 Patented new technology eliminates the body to lid edge extrusion, replacing it with an innovative folded rim design which makes the rack stronger, lighter yet more water and dust resistant.

• Constructed from high-tensile aluminum alloy, this 19 inch ruggedized electronic transit rack has been designed for defense and commercial applications, when light weight and strong protection against physical, climatic and electromagnetic hazards are required.



NEW

	External Size (in)				£ .						
Part Number	zi ^{čt}	O T	Aight.	Jrieff	The State of the S	10 Miles	4ight	Z No.	Con Contract		
RR0319-0303	11.2	28.4	23.2	3	18.9	4.3	28.1	4	8		
RR0324-0303	11.2	33.5	23.2	3	24.0	5.0	30.6	4	8		
RR0329-0303	11.2	38.6	23.2	3	29.1	5.8	33.0	4	8		
RR0334-0303	11.2	43.7	23.2	3	34.3	6.6	35.5	4	8		
RR0419-0303	13.0	28.4	23.2	4	18.9	4.9	29.7	4	8		
RR0424-0303	13.0	33.5	23.2	4	24.0	5.8	32.2	4	8		
RR0429-0303	13.0	38.6	23.2	4	29.1	6.7	34.8	4	8		
RR0434-0303	13.0	43.7	23.2	4	34.3	7.6	37.4	4	8		
RR0519-0303	14.7	28.4	23.2	5	18.9	5.6	31.2	4	8		
RR0524-0303	14.7	33.5	23.2	5	24.0	6.6	33.9	4	8		
RR0529-0303	14.7	38.6	23.2	5	29.1	7.6	36.6	4	8		
RR0534-0303	14.7	43.7	23.2	5	34.3	8.6	39.2	4	8		
RR0619-0303	16.4	28.4	23.2	6	18.9	6.3	32.8	4	8		
RR0624-0303	16.4	33.5	23.2	6	24.0	7.4	35.6	4	8		
RR0629-0303	16.4	38.6	23.2	6	29.1	8.5	38.3	4	8		
RR0634-0303	16.4	43.7	23.2	6	34.3	9.6	41.1	4	8		
BB0010 0000		00.4	000				2.7				
RR0819-0303	19.9	28.4	23.2	8	18.9	7.6	36.7	4	12		
RR0824-0303	19.9	33.5	23.2	8	24.0	9.0	39.7	4	12		
RR0829-0303	19.9	38.6	23.2	8	29.1	10.3	42.6	4	12		
RR0834-0303	19.9	43.7	23.2	8	34.3	11.7	45.6	4	12		
BB1010 0202	22.4	20.4	22.2	1.0	100	0.0	20.0		10		
RR1019-0303	23.4	28.4	23.2	10	18.9	8.9	39.8	4	12		
RR1024-0303	23.4	33.5	23.2	10	24.0	10.5	43.0	4	12		
RR1029-0303	23.4	38.6	23.2	10	29.1	12.1	46.2	4	12		
RR1034-0303	23.4	43.7	23.2	10	34.3	13.7	49.3	4	12		
DD1210 0202	240	20.4	22.2	10	100	10.2	12.0	4	10		
RR1219-0303	26.9	28.4	23.2	12	18.9	10.3	43.0	4	12		
RR1224-0303	26.9	33.5	23.2	12	24.0	12.1	46.4	4	12		
RR1229-0303	26.9	38.6	23.2	12	29.1	14.0	49.7	4	12		
RR1234-0303	26.9	43.7	23.2	12	34.3	15.8	53.1	4	12		

Available as full and half rack

5 inch lids available as alternative to 3 inch std lids.

V10.05 Created May 2010 E&OE. All information believed to be correct at time of publication. No liability accepted for decisions made as a result of errors. Specifications may change without notice.