

ZERO KNOWS

19" RACKMOUNT CASES

WARRIOR™ WITH SHOCK MOUNTS, DOUBLE ENTRY

BUYERS GUIDE AND PART NUMBER BUILDER
SELECT CASE SIZES AND OPTIONS. CUSTOM PARTS & BUILDS ARE AVAILABLE

CASE NUMBER

ZDR **U SIZE** **BODY** **RACK** **FRONT** **REAR**

U SIZE
☐ 04-4U ☐ 10-10U
☐ 05-5U ☐ 11-11U
☐ 06-6U ☐ 12-12U
☐ 07-7U ☐ 13-13U
☐ 08-8U ☐ 14-14U
☐ 09-9U ☐ 15-15U

BODY DEPTH
☐ 21" ☐ 24" ☐ 27" ☐ 30"

RACK DEPTH
☐ 18-18"/457 mm
☐ 21-21"/534 mm
☐ 24-24"/610 mm
☐ 27-27"/686 mm
☐ 30-30"/762 mm

COVERS (INTERIOR DEPTH)
☐ 03-3"/76 mm
☐ 05-5"/127 mm

COLORS
☐ BK-Black 27040
☐ DB-Dark Blue 25102
☐ DS-Desert Sand 20372
☐ FG-Forest Green 24052
☐ GR-Gray 26270
☐ MR-Maroon PMS 202 ☐ MB-Medium Blue 25190 ☐ NA-Natural
☐ NG-NATO Green RAL6014
☐ OD-Olive Drab 24097
☐ OR-Orange 21400
☐ RD-Red 21105
☐ WH-White 27925
☐ YW-Yellow 23785
 FED-STD-595 for reference.

SHOCK MOUNTS (EQUIPMENT WEIGHT)
☐ 01-20 to 49 lbs ☐ 02-50 to 80 lbs
☐ 03-81 to 150 lbs
☐ 04-151 to 250 lbs ☐ 05-251 to 350 lbs
 Call for loads over 350 lbs.

ENVIRONMENT
☐ 00-None Required
☐ HI-Humidity Indicator
☐ PV-Pressure Valve
COMBINATIONS
☐ PH-PV and HI
☐ WT-Watertight, PV ☐ WV-WT, HI, PV

RACK HOLES
☐ 00-Standard EIA
☐ M5-M5 Metric Tapped ☐ M6-M6 Metric Tapped ☐ SQ-Square

SHELVES/DRAWERS
☐ 00-None Required
☐ EA-Equipment Angles
☐ FS-Fixed Shelf
☐ IR-Intermediate Rails
☐ KT-Keyboard Tray ☐ RS-Rack Slides
☐ SD-Sliding Drawer
☐ SF-Sliding Shelf

OTHER OPTIONS
☐ 00-None Required
☐ CA-Removable Casters (4)
☐ CH-Card Holder
☐ CR-Chair ☐ CS-Coupling Straps
☐ LR-Lifting/Tie Down Rings ☐ SP-Storage Pouch
☐ TB-Table

COMBINATIONS
☐ Z1-CH, SP
☐ Z2-CA, CS
☐ Z3-CA, CH, CS, SP
☐ Z4-CA, CH, CS, LR, SP
☐ Z5-CH, LR
☐ Z6-CS, SP
☐ ZC-CA, LR
☐ ZD-CA, CH, LR
☐ ZE-CA, CH, LR, SP
☐ ZF-CA, SP

THE ZERO WARRIOR™ RACKMOUNT CASE
 is a rotomolded, double entry case designed and engineered to provide complete protection for the most sensitive E.I.A 19" rackmountable equipment and instrumentation.
 WARRIOR Rackmount cases meet the rigors of virtually all conditions including extreme temperatures, altitude, rain, sleet, snow, sand, and dust. Protection unparalleled in the industry. These cases are also available through our Quick-Ship Program. Details available at: www.zerocases.com/quickship

STANDARD RACKFRAME LOAD RANGES

Shock Mounts Per System	Load Ranges (lbs/kg) For Equipment Installed in Rack
8 ea	20 to 49 lbs / 9.1 to 22.2 kg
8 ea	50 to 80 lbs / 22.7 to 36.3 kg
8 ea	81 to 150 lbs / 36.8 to 68.1 kg
16 ea	151 to 250 lbs / 68.6 to 113.5 kg
16 ea	251 to 340 lbs / 113.8 to 154.2 kg

Standard Equipment Load Ranges


Contact Sierra Cases for engineering assistance, questions and specific colors. Call 888.880.7728.


Lifting Rings: Verify the application does not exceed the load carrying capacity of the lifting rings or case.
Stacking: Verify weight and support.
Shock Mounts: Equipment loads over 150 lbs (68 kg).




NOTES:
☐ Watertight Option not available with Locking Hasps.
☐ Select #01 Shock Mounts for 21" Case Body.
☐ Quick-Ship not available. Requires additional lead time.



Sierra Cases | 6140 S. Gun Club Road, Aurora, CO 80016
 888-880-7728 | sales@sierracases.com | SierraCases.com

EIA UNITS in/mm A	BODY DEPTH in/mm B	RACK DEPTH in/mm C	COVER HEIGHT in/mm D + E	CASE HEIGHT in/mm F	VOLUME cubic ft/m	WEIGHT lb/kg	SWAY + / -	QUICK SHIP	ZERO PART #	NSN	WARRIOR ZDR 4U-6U
4U 7.12" (181 mm)	21/534	18/457	9/229	16.00/406	7.7/.22	51.0/23.1			ZDR042118-0303		WARRIOR ZDR Shock Mount includes a 19" Rack. All weights are approximate. Std load range: 20-80 lbs (9.1-36.3 kg) +/- = Sway space to be increased or decreased dependent on customer selection. ☒ = Decreased Sway Space QS = Quick-Ship is Available Drawing Specifications: Cover Height: 03 = 4.5 in (114.3 mm) (Exterior) 05 = 6.5 in (165.1 mm) Inside Depth: 03 = 3.0 in (76.2 mm) 05 = 5.0 in (127 mm) Case Width G = 27.25 in (692 mm)     Custom sizes and colors available on special order.
			11/279		7.9/.22	52.0/23.5			ZDR042118-0305		
			13/330		8.4/.24	54.0/24.5			ZDR042118-0505		
		21/534	9/229		7.7/.22	51.0/23.1			ZDR042121-0303		
			11/279		7.9/.22	52.0/23.5			ZDR042121-0305		
			13/330		8.4/.24	54.0/24.5			ZDR042121-0505		
	24/610	21/534	9/229	16.00/406	8.4/.24	54.0/24.5			ZDR042421-0303		
			11/279		8.7/.25	55.0/24.9			ZDR042421-0305		
			13/330		9.2/.26	57.0/25.9			ZDR042421-0505		
		24/610	9/229		8.4/.24	54.0/24.5			ZDR042424-0303		
			11/279		8.7/.25	55.0/24.9			ZDR042424-0305		
			13/330		9.2/.26	57.0/25.9			ZDR042424-0505		
	27/686	24/610	9/229	16.00/406	9.1/.26	57.0/25.9		QS	ZDR042724-0303	8145-01-582-5650	
			11/279		9.5/.27	58.0/26.3		QS	ZDR042724-0305	8145-01-582-5666	
			13/330		10.0/.28	60.0/27.3		QS	ZDR042724-0505		
		27/686	9/229		9.1/.26	57.0/25.9			ZDR042727-0303		
			11/279		9.5/.27	58.0/26.3			ZDR042727-0305		
			13/330		10.0/.28	60.0/27.3			ZDR042727-0505		
	30/762	27/686	9/229	16.00/406	9.8/.28	60.0/27.3		QS	ZDR043027-0303	8145-01-582-5683	
			11/279		10.3/.29	61.0/27.7		QS	ZDR043027-0305	8145-01-582-5684	
			13/330		10.8/.31	63.0/28.6		QS	ZDR043027-0505		
		30/762	9/229		9.8/.28	60.0/27.3			ZDR043030-0303		
			11/279		10.3/.29	61.0/27.7			ZDR043030-0305		
			13/330		10.8/.31	63.0/28.6			ZDR043030-0505		
5U 8.87" (225 mm)	21/534	18/457	9/229	17.75/451	7.6/.22	61.0/27.7			ZDR052118-0303		
			11/279		9.0/.25	62.0/28.1			ZDR052118-0305		
			13/330		9.3/.26	64.0/29.0			ZDR052118-0505		
		21/534	9/229		7.6/.22	61.0/27.7			ZDR052121-0303		
			11/279		9.0/.25	62.0/28.1			ZDR052121-0305		
			13/330		9.3/.26	64.0/29.0			ZDR052121-0505		
	24/610	21/534	9/229	17.75/451	8.7/.25	64.0/29.5			ZDR052421-0303		
			11/279		9.8/.28	65.0/30.0			ZDR052421-0305		
			13/330		10.2/.29	67.0/30.4			ZDR052421-0505		
		24/610	9/229		8.7/.25	64.0/29.5			ZDR052424-0303		
			11/279		9.8/.28	65.0/30.0			ZDR052424-0305		
			13/330		10.2/.29	67.0/30.4			ZDR052424-0505		
	27/686	24/610	9/229	17.75/451	9.8/.28	67.0/30.4		QS	ZDR052724-0303	8145-01-582-5687	
			11/279		10.6/.30	68.0/30.9		QS	ZDR052724-0305	8145-01-582-5690	
			13/330		11.1/.31	70.0/31.8		QS	ZDR052724-0505		
		27/686	9/229		9.8/.28	67.0/30.4			ZDR052727-0303		
			11/279		10.6/.30	68.0/30.9			ZDR052727-0305		
			13/330		11.1/.31	70.0/31.8			ZDR052727-0505		
	30/762	27/686	9/229	17.75/451	10.9/.31	70.0/31.8		QS	ZDR053027-0303	8145-01-582-5691	
			11/279		11.4/.32	71.0/32.2		QS	ZDR053027-0305	8145-01-582-5435	
			13/330		12.0/.34	73.0/33.1		QS	ZDR053027-0505		
		30/762	9/229		10.9/.31	70.0/31.8			ZDR053030-0303		
			11/279		11.4/.32	71.0/32.2			ZDR053030-0305		
			13/330		12.0/.34	73.0/33.1			ZDR053030-0505		
6U 10.63" (270 mm)	24/610	21/534	9/229	17.75/451	9.9/.28	60.0/27.2	+/-		ZDR062421-0303		
			11/279		10.3/.29	61.0/27.7	+/-		ZDR062421-0305		
			13/330		11.1/.31	63.0/28.6	+/-		ZDR062421-0505		
		24/610	9/229		9.9/.28	60.0/27.2	+/-		ZDR062424-0303		
			11/279		10.3/.29	61.0/27.7	+/-		ZDR062424-0305		
			13/330		11.1/.31	63.0/28.6	+/-		ZDR062424-0505		
	27/686	24/610	9/229	17.75/451	10.8/.31	63.0/28.6	+/-	QS	ZDR062724-0303	8145-01-582-5438	
			11/279		11.3/.32	64.0/29.1	+/-	QS	ZDR062724-0305	8145-01-582-5447	
			13/330		12.0/.34	66.0/30.0	+/-	QS	ZDR062724-0505		
		27/686	9/229		10.8/.31	63.0/28.6	+/-		ZDR062727-0303		
			11/279		11.3/.32	64.0/29.1	+/-		ZDR062727-0305		
			13/330		12.0/.34	66.0/30.0	+/-		ZDR062727-0505		
	30/762	27/686	9/229	17.75/451	11.7/.33	66.0/30.0	+/-	QS	ZDR063027-0303	8145-01-582-5454	
			11/279		12.3/.35	67.0/30.4	+/-	QS	ZDR063027-0305	8145-01-582-5460	
			13/330		12.9/.37	69.0/31.4	+/-	QS	ZDR063027-0505		
		30/762	9/229		11.7/.33	66.0/30.0	+/-		ZDR063030-0303		
			11/279		12.3/.35	67.0/30.4	+/-		ZDR063030-0305		
			13/330		12.9/.37	69.0/31.4	+/-		ZDR063030-0505		

EIA UNITS in/mm A	BODY DEPTH in/mm B	RACK DEPTH in/mm C	COVER HEIGHT in/mm D + E	CASE HEIGHT in/mm F	VOLUME cubic ft/m	WEIGHT lb/kg	SWAY + / -	QUICK SHIP	ZERO PART #	NSN	WARRIOR ZDR 7U-10U
7U 12.37" (314 mm)	24/610	21/534	9/229	21.25/540	11.0/.31	64.0/29.0			ZDR072421-0303		WARRIOR ZDR Shock Mount includes a 19" Rack. All weights are approximate. Std load range: 20-80 lbs (9.1-36.3 kg) +/- = Sway space to be increased or decreased dependent on customer selection. ▼ = Decreased Sway Space QS = Quick-Ship is Available Drawing Specifications: Cover Height: 03 = 4.5 in (114.3 mm) (Exterior) 05 = 6.5 in (165.1 mm) Inside Depth: 03 = 3.0 in (76.2 mm) 05 = 5.0 in (127 mm) Case Width G = 27.25 in (692 mm)
			11/279		11.7/.33	65.0/29.4			ZDR072421-0305		
			13/330		12.4/.35	67.0/30.4			ZDR072421-0505		
		24/610	9/229		11.0/.31	64.0/29.0			ZDR072424-0303		
			11/279		11.7/.33	65.0/29.4			ZDR072424-0305		
			13/330		12.4/.35	67.0/30.4			ZDR072424-0505		
	27/686	24/610	9/229	21.25/540	12.0/.34	66.0/30.0		QS	ZDR072724-0303	8145-01-582-5467	
			11/279		12.7/.36	67.0/30.4		QS	ZDR072724-0305	8145-01-582-5476	
			13/330		13.4/.38	69.0/31.4		QS	ZDR072724-0505		
		27/686	9/229		12.0/.34	66.0/30.0			ZDR072727-0303		
			11/279		12.7/.36	67.0/30.4			ZDR072727-0305		
			13/330		13.4/.38	69.0/31.4			ZDR072727-0505		
	30/762	27/686	9/229	21.25/540	13.0/.37	68.0/30.9		QS	ZDR073027-0303	8145-01-582-5488	
			11/279		13.7/.39	69.0/31.4		QS	ZDR073027-0305	8145-01-582-5496	
			13/330		14.4/.41	71.0/32.2		QS	ZDR073027-0505		
		30/762	9/229		13.0/.37	68.0/30.9			ZDR073030-0303		
			11/279		13.7/.39	69.0/31.4			ZDR073030-0305		
			13/330		14.4/.41	71.0/32.2			ZDR073030-0505		
8U 14.12" (358 mm)	24/610	21/534	9/229	21.25/540	11.9/.34	69.0/31.4	+/-		ZDR082421-0303		   
			11/279		12.6/.36	70.0/31.8	+/-		ZDR082421-0305		
			13/330		13.4/.38	72.0/32.7	+/-		ZDR082421-0505		
		24/610	9/229		11.9/.34	69.0/31.4	+/-		ZDR082424-0303		
			11/279		12.6/.36	70.0/31.8	+/-		ZDR082424-0305		
			13/330		13.4/.38	72.0/32.7	+/-		ZDR082424-0505		
	27/686	24/610	9/229	21.25/540	13.0/.37	71.0/32.2	+/-	QS	ZDR082724-0303	8145-01-582-5218	
			11/279		13.7/.39	72.0/32.7	+/-	QS	ZDR082724-0305	8145-01-582-5155	
			13/330		14.5/.41	74.0/33.6	+/-	QS	ZDR082724-0505		
		27/686	9/229		13.0/.37	71.0/32.2	+/-		ZDR082727-0303		
			11/279		13.7/.39	72.0/32.7	+/-		ZDR082727-0305		
			13/330		14.5/.41	74.0/33.6	+/-		ZDR082727-0505		
	30/762	27/686	9/229	21.25/540	14.1/.40	73.0/33.1	+/-	QS	ZDR083027-0303	8145-01-582-5241	
			11/279		14.8/.42	74.0/33.6	+/-	QS	ZDR083027-0305	8145-01-582-5278	
			13/330		15.6/.44	76.0/34.5	+/-	QS	ZDR083027-0505		
		30/762	9/229		14.1/.40	73.0/33.1	+/-		ZDR083030-0303		
			11/279		14.8/.42	74.0/33.6	+/-		ZDR083030-0305		
			13/330		15.6/.44	76.0/34.5	+/-		ZDR083030-0505		
9U 15.87" (403 mm)	24/610	21/534	9/229	24.75/629	12.2/.35	75.0/34.1			ZDR092421-0303		 
			11/279		13.6/.38	76.0/34.5			ZDR092421-0305		
			13/330		14.3/.40	78.0/35.4			ZDR092421-0505		
		24/610	9/229		12.2/.35	75.0/34.1			ZDR092424-0303		
			11/279		13.6/.38	76.0/34.5			ZDR092424-0305		
			13/330		14.3/.40	78.0/35.4			ZDR092424-0505		
	27/686	24/610	9/229	24.75/629	13.7/.39	77.0/35.0		QS	ZDR092724-0303	8145-01-582-5317	
			11/279		14.8/.42	78.0/35.4		QS	ZDR092724-0305	8145-01-582-5325	
			13/330		15.6/.44	80.0/36.3		QS	ZDR092724-0505		
		27/686	9/229		13.7/.39	77.0/35.0			ZDR092727-0303		
			11/279		14.8/.42	78.0/35.4			ZDR092727-0305		
			13/330		15.6/.44	80.0/36.3			ZDR092727-0505		
	30/762	27/686	9/229	24.75/629	15.2/.43	79.0/35.0		QS	ZDR093027-0303	8145-01-582-5333	
			11/279		16.0/.45	80.0/35.4		QS	ZDR093027-0305	8145-01-582-5339	
			13/330		16.7/.47	82.0/36.6		QS	ZDR093027-0505		
		30/762	9/229		15.2/.43	79.0/35.0			ZDR093030-0303		
			11/279		16.0/.45	80.0/35.4			ZDR093030-0305		
			13/330		16.7/.47	82.0/36.6			ZDR093030-0505		
10U 17.62" (448 mm)	24/610	21/534	9/229	24.75/629	13.7/.39	79.0/35.8	+/-		ZDR102421-0303		 
			11/279		14.5/.41	80.0/36.2	+/-		ZDR102421-0305		
			13/330		15.5/.44	82.0/37.3	+/-		ZDR102421-0505		
		24/610	9/229		13.7/.39	79.0/35.8	+/-		ZDR102424-0303		
			11/279		14.5/.41	80.0/36.2	+/-		ZDR102424-0305		
			13/330		15.5/.44	82.0/37.3	+/-		ZDR102424-0505		
	27/686	24/610	9/229	24.75/629	15.0/.42	81.0/36.8	+/-	QS	ZDR102724-0303	8145-01-582-5129	
			11/279		15.8/.45	82.0/37.2	+/-	QS	ZDR102724-0305	8145-01-582-5081	
			13/330		16.7/.47	84.0/38.2	+/-	QS	ZDR102724-0505		
		27/686	9/229		15.0/.42	81.0/36.8	+/-		ZDR102727-0303		
			11/279		15.8/.45	82.0/37.2	+/-		ZDR102727-0305		
			13/330		16.7/.47	84.0/38.2	+/-		ZDR102727-0505		
	30/762	27/686	9/229	24.75/629	16.3/.46	83.0/37.6	+/-	QS	ZDR103027-0303	8145-01-582-7460	
			11/279		17.1/.48	84.0/38.2	+/-	QS	ZDR103027-0305	8145-01-582-7486	
			13/330		17.9/.51	86.0/39.1	+/-	QS	ZDR103027-0505		
		30/762	9/229		16.3/.46	83.0/37.6	+/-		ZDR103030-0303		
			11/279		17.1/.48	84.0/38.2	+/-		ZDR103030-0305		
			13/330		17.9/.51	86.0/39.1	+/-		ZDR103030-0505		

EIA UNITS in/mm A	BODY DEPTH in/mm B	RACK DEPTH in/mm C	COVER HEIGHT in/mm D + E	CASE HEIGHT in/mm F	VOLUME cubic ft/m	WEIGHT lb/kg	SWAY + / -	QUICK SHIP	ZERO PART #	NSN	WARRIOR ZDR 11U-15U
11U 19.38" (492 mm)	24/610	21/534	9/229	28.25/718	14.7/.42	80.0/36.2			ZDR112421-0303		WARRIOR ZDR Shock Mount includes a 19" Rack. All weights are approximate. Std load range: 20-80 lbs (9.1-36.3 kg) +/- = Sway space to be increased or decreased dependent on customer selection. ▼ = Decreased Sway Space QS = Quick-Ship is Available Drawing Specifications: Cover Height: 03 = 4.5 in (114.3 mm) (Exterior) 05 = 6.5 in (165.1 mm) Inside Depth: 03 = 3.0 in (76.2 mm) 05 = 5.0 in (127 mm) Case Width G = 27.25 in (692 mm)
			11/279		15.6/.44	81.0/36.6			ZDR112421-0305		
			13/330		16.5/.47	83.0/37.6			ZDR112421-0505		
		24/610	9/229		14.7/.42	80.0/36.2			ZDR112424-0303		
			11/279		15.6/.44	81.0/36.6			ZDR112424-0305		
			13/330		16.5/.47	83.0/37.6			ZDR112424-0505		
	27/686	24/610	9/229	28.25/718	16.0/.45	82.0/37.2		QS	ZDR112724-0303	8145-01-582-7491	
			11/279		16.9/.48	83.0/37.6		QS	ZDR112724-0305	8145-01-582-7683	
			13/330		17.8/.50	85.0/38.6		QS	ZDR112724-0505		
		27/686	9/229		16.0/.45	82.0/37.2			ZDR112727-0303		
			11/279		16.9/.48	83.0/37.6			ZDR112727-0305		
			13/330		17.8/.50	85.0/38.6			ZDR112727-0505		
	30/762	27/686	9/229	28.25/718	17.3/.49	84.0/38.2		QS	ZDR113027-0303	8145-01-582-7690	
			11/279		18.2/.52	85.0/38.6		QS	ZDR113027-0305	8145-01-582-7725	
			13/330		19.1/.54	87.0/39.5		QS	ZDR113027-0505		
		30/762	9/229		17.3/.49	84.0/38.2			ZDR113030-0303		
			11/279		18.2/.52	85.0/38.6			ZDR113030-0305		
			13/330		19.1/.54	87.0/39.5			ZDR113030-0505		
12U 21.25" (536 mm)	24/610	21/534	9/229	28.25/718	15.6/.44	80.0/36.2	▼		ZDR122421-0303		   
			11/279		16.5/.47	81.0/36.6	▼		ZDR122421-0305		
			13/330		17.5/.50	83.0/37.6	▼		ZDR122421-0505		
		24/610	9/229		15.6/.44	80.0/36.2	▼		ZDR122424-0303		
			11/279		16.5/.47	81.0/36.6	▼		ZDR122424-0305		
			13/330		17.5/.50	83.0/37.6	▼		ZDR122424-0505		
	27/686	24/610	9/229	28.25/718	17.0/.48	82.0/37.2	▼	QS	ZDR122724-0303		
			11/279		17.9/.51	83.0/37.6	▼	QS	ZDR122724-0305		
			13/330		18.9/.53	85.0/38.6	▼	QS	ZDR122724-0505	6625-01-543-2932	
		27/686	9/229		17.0/.48	82.0/37.2	▼		ZDR122727-0303		
			11/279		17.9/.51	83.0/37.6	▼		ZDR122727-0305		
			13/330		18.9/.53	85.0/38.6	▼		ZDR122727-0505		
	30/762	27/686	9/229	28.25/718	18.4/.52	84.0/38.2	▼	QS	ZDR123027-0303	8145-01-582-7730	
			11/279		19.3/.55	85.0/38.6	▼	QS	ZDR123027-0305	8145-01-582-7734	
			13/330		20.3/.57	87.0/39.5	▼	QS	ZDR123027-0505		
		30/762	9/229		18.4/.52	84.0/38.2	▼		ZDR123030-0303		
			11/279		19.3/.55	85.0/38.6	▼		ZDR123030-0305		
			13/330		20.3/.57	87.0/39.5	▼		ZDR123030-0505		
14U 24.62" (625 mm)	24/610	21/534	9/229	33.50/785	17.2/.49	85.0/38.6			ZDR142421-0303		   
			11/279		18.4/.52	86.0/39.1			ZDR142421-0305		
			13/330		19.3/.55	88.0/40.0			ZDR142421-0505		
		24/610	9/229		17.2/.49	85.0/38.6			ZDR142424-0303		
			11/279		18.4/.52	86.0/39.1			ZDR142424-0305		
			13/330		19.3/.55	88.0/40.0			ZDR142424-0505		
	27/686	24/610	9/229	33.50/785	18.9/.53	87.0/39.5		QS	ZDR142724-0303	8145-01-582-7898	
			11/279		20.0/.57	88.0/40.0		QS	ZDR142724-0305	8145-01-582-8177	
			13/330		21.0/.59	90.0/40.9		QS	ZDR142724-0505		
		27/686	9/229		18.9/.53	87.0/39.5			ZDR142727-0303		
			11/279		20.0/.57	88.0/40.0			ZDR142727-0305		
			13/330		21.0/.59	90.0/40.9			ZDR142727-0505		
	30/762	27/686	9/229	33.50/785	20.6/.58	89.0/40.5		QS	ZDR143027-0303		
			11/279		21.6/.61	90.0/40.9		QS	ZDR143027-0305		
			13/330		22.7/.64	92.0/41.8		QS	ZDR143027-0505	5895-01-552-9388	
		30/762	9/229		20.6/.58	89.0/40.5			ZDR143030-0303		
			11/279		21.6/.61	90.0/40.9			ZDR143030-0305		
			13/330		22.7/.64	92.0/41.8			ZDR143030-0505		
15U 26.37" (670 mm)	24/610	21/534	9/229	33.50/851	18.4/.52	85.0/38.7	▼		ZDR152421-0303		   
			11/279		19.3/.55	86.0/39.1	▼		ZDR152421-0305		
			13/330		20.6/.58	88.0/40.0	▼		ZDR152421-0505		
		24/610	9/229		18.4/.52	85.0/38.7	▼		ZDR152424-0303		
			11/279		19.3/.55	86.0/39.1	▼		ZDR152424-0305		
			13/330		20.6/.58	88.0/40.0	▼		ZDR152424-0505		
	27/686	24/610	9/229	33.50/851	20.0/.57	87.0/39.5	▼	QS	ZDR152724-0303	8145-01-582-8182	
			11/279		21.0/.59	88.0/40.0	▼	QS	ZDR152724-0305	8145-01-582-8187	
			13/330		22.2/.63	90.0/40.9	▼	QS	ZDR152724-0505		
		27/686	9/229		20.0/.57	87.0/39.5	▼		ZDR152727-0303		
			11/279		21.0/.59	88.0/40.0	▼		ZDR152727-0305		
			13/330		22.2/.63	90.0/40.9	▼		ZDR152727-0505		
	30/762	27/686	9/229	33.50/851	21.6/.61	89.0/40.5	▼	QS	ZDR153027-0303	8145-01-582-8263	
			11/279		22.7/.64	90.0/40.9	▼	QS	ZDR153027-0305	8145-01-582-8276	
			13/330		23.8/.67	92.0/41.8	▼	QS	ZDR153027-0505		
		30/762	9/229		21.6/.61	89.0/40.5	▼		ZDR153030-0303		
			11/279		22.7/.64	90.0/40.9	▼		ZDR153030-0305		
			13/330		23.8/.67	92.0/41.8	▼		ZDR153030-0505		